












## Interface Compatibility

Interface	 All TI-Nspire™ handhelds and software	 All TI-Nspire™ CAS handhelds and software	 All TI-Nspire™ handhelds with TI-84 Keypad
 TI-Nspire Lab Cradle	●	●	
 CBL 2™			●
 Vernier LabPro®			●
 Vernier EasyLink®/Go! Link interfaces	●	●	●
 CBR 2™ Vernier Go! Motion detector	●	●	●
 Vernier EasyTemp®/Go! Temp sensors	●	●	●

## Data Collection Interface Comparison

Product	 TI-Nspire Lab Cradle	 CBL 2
Remote data collection	Standalone with TI-Nspire & TI-Nspire CX Family handhelds	Standalone with TI graphing calculator
Supported Platforms	Calculator, Computer, Standalone	Calculator & Standalone
Number of Samples per Second	100,000	50,000
Internal Data Storage	32 MB	12,000 points
Resolution	12 bit	10 bit
Sensor Ports	5 (3 analog & 2 digital)	4 (2 analog & 2 digital)
Number of Compatible Vernier Sensors	Over 50	Over 40
Sensors included	None	Light, temperature & voltage
Use with Motion Detectors, Photogates	Yes	Yes
Analog Output	No	Yes
Suggested Retail Price	\$180	\$240
Power	TI-Nspire Rechargeable Battery	AA alkaline

### For more information:

ti-cares@ti.com

1.800.TI.CARES

[education.ti.com/support](http://education.ti.com/support)

©2011 Texas Instruments WEB11150.2



Your Passion. Our Technology. Student Success.™